According to Regulation (EC) 1907/2006 and Regulation (EC) 453/2010 (REACH)

Version: 1.0

### BREMSENREINIGER

Revision date: 18.03.2014

### Identification of the substance/mixture and of the company/undertaking

#### 1.1. **Product identifier:**

Trade name: **Bremsenreiniger** 

#### Relevant identified uses of the substance or mixture and uses advised against:

Use of the substance

/Mixture: cleaner agent

#### 1.3. Details of the supplier of the safety data sheet:

FOLIATEC Böhm GmbH & Co. Vertriebs KG

Neumeyerstraße 70

D-90411 Nürnberg

### Further information obtainable from:

Abteilung Produkttechnik techsupport@foliatec.de

#### **Emergency telephone number:**

+49 - 91 19 75 44 - 0

(Monday to Friday, 08:00 - 17:00)

#### **Hazard identification**

#### 2.1. Classification of the substance or mixture:

#### Classification (EC) 1272/2008

Flam. Aerosol 1; H222 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H336 Aquatic Chronic 2; H411

### Classification (67/548/EEC, 1999/45/EC)

F+; R12 Xi; R38 R67

N; R51/53

#### 2.2. Label elements:

### Label elements (CLP)





GHS07

GHS09

Signal word: Danger

### Hazard statements:

Extremely flammable aerosol. H222 H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects. H411

### Precautionary statements:

P102 Keep out of reach of children.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray. P261

According to Regulation (EC) 1907/2006 and Regulation (EC) 453/2010 (REACH)

Version: 1.0

# BREMSENREINIGER

Revision date: 18.03.2014

P271 Use only outdoors or in a well-ventilated area.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P403 Store in a well-ventilated place.

Contains: Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclic, Acetone

Text for labelling:

Whatever its contents: 'Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Contain: > 30% hydrocarbons

#### Label elements (67/548/EEC or 1999/45/EC)

F+



Extremely flammable



Irritant



Dangerous for the environment

R-phrases:

R12 Extremely flammable. R38 Irritating to skin.

R67 Vapours may cause drowsiness and dizziness.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases:

S23 Do not breathe spray.

S24/25 Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of insufficient ventilation, wear suitable respiratory equipment.

Use only in well-ventilated areas.

S61 Avoid release to the environment. Refer to special instructions / Safety data sheets.

Hazardous compounents which must be listed on the label:

/

Text for labelling:

Whatever its contents: 'Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Contain: > 30% aliphatic hydrocarbons

#### 2.3. Other hazards:

No data available.

3. Composition/information on ingred	dients				
Substance:					
Mixture: 🗵					
Chemical name:	Content (% m/m):	CAS: EC: Index:	Classification (67/548/EC):	Classification (1272/2008/EC):	

According to Regulation (EC) 1907/2006 and Regulation (EC) 453/2010 (REACH)

Version: 1.0

Revision date: 18.03.2014

### BREMSENREINIGER

Hydrocarbons, C7, n-alkanes, iso- alkanes, cyclic	50 – 100	/ 927-510-4 /	F; R11, Xn; R65, Xi; R38, R67, N; R51/53	Flam. Liq. 2; H225, Asp. Tox. 1; H304, Skin Irrit. 2; H315, STOT SE 3; H336, Aquatic Chronic 2; H411
Aceton	10 – 25	67-64-1 200-827-9 649-328-00-1	F; R11, Xi; R36, R66-67	Flam. Liq. 2; H225, Eye Irrit. 2; H319, STOTE SE 3; H336
Carbon dioxide	2,5 – 10	124-38-9 204-696-9	/	Press. Gass: H280
Propane	2,5 – 10	74-98-6 200-827-9 601-003-00-5	F+; R12	Flam. Gas. 1; H220, Press. Gass; H280
Isobutane	2,5 – 10	75-28-5 200-857-2 601-004-00-0	F+; R12	Flam. Gas. 1; H220, Press. Gass; H280

### 4. First aid measures

### 4.1. Description of first measures:

General advice:

If inhaled remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for

additional treatment.

In case of skin contact remove contaminated clothing. Flush exposed area with water and follow by washing with soap if

available.

In case of eye contact Flush eyes with water while holding eyelids open. Rest eyes for 30 minutes. If redness, burning,

blurred vision, or swelling persist, transport to the nearest medical facility for additional treatment.

If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If

vomiting occurs spontaneously, keep head below hips to prevent aspiration.

#### 4.2. Most important symptoms and effects, both acute and delayed:

Drowsiness and dizziness. Irritation and dermatitis, weakness.

### 4.3. Indification of any immediate medical attention and special treatment needed:

No data available.

### 5. Firefighting measures

### 5.1. Extinguishing media:

Suitable extinguishing Foam, water spray or fog. Dry chemical powder, carbon dioxide.

media:

Unsuitable Water jet.

extinguishing media

#### **5.2.** Special hazards arising from the substance or mixture:

Specific hazars during Exposure to decomposition products may cause health problems. Possible in case of fire / high

fire fighting: temperatures the formation of hazardous / toxic fumes.

According to Regulation (EC) 1907/2006 and Regulation (EC) 453/2010 (REACH)

Version: 1.0

### BREMSENREINIGER

Revision date: 18.03.2014

#### 5.3. Advice for firefighters:

Besondere In the event of fire, self-contained breathing apparatus. Personal protective equipment.

Schutzausrüstung für die Brandbekämpfung:

Weitere Information: Standard procedure for chemical fires. Fighting measures that suit the environment. Explosion and

fire fumes do not breathe. Use water spray to cool unopened containers. Collect contaminated firefighting water separately, do not empty into drains. Fire residues and contaminated firefighting water must be disposed in according to local regulations. Pay attention to flashback. Because of the

high vapor pressure when heated bursting of the vessels.

#### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures:

Refer to protective measures listed in sections 7 and 8 Personal protective equipment. Remove all sources of ignition. Avoid contact with eyes and skin. Ensure adequate ventilation, especially in confined spaces. Personnel evacuate immediately to safe place. Avoid inhalation of vapors or mists . Himself against vapors accumulating to form explosive concentrations, beware. Vapors may accumulate in low lying areas.

#### **6.2.** Environmental precautions:

Do not flush into surface water or sanitary sewer. Prevent further leakage or spillage if possible without risk. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3. Methods and material for containment and cleaning up:

Contain spilled liquid with sand, earth or other suitable absorbents. Recover free liquid in suitable containers. Clean contaminated area. Dispose of according to local regulations.

#### **6.4.** Reference to other sections:

See section: 7, 8, 11, 12 and 13.

### 7. Handling and storage

#### 7.1. Precautions for safe handling:

Advice on safe handling:

Inventory levels at the workplace must be restricted. Use only in well ventilated areas. Vapors and spray mists. Avoid contact with eyes and skin. Do not spray on a naked flame or any incandescent material. Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor exposure limits. Measures against electrostatic discharges. Personal protective equipment see

section 8

Advice on protection against fire and explosion

Normal measures for preventive fire protection. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Keep away from heat and ignition sources. Do not smoke. Sparking tools. Electrical equipment should be protected to the appropriate standards.

### 7.2. Conditions for safe storage, including any incompatibilities:

Requirements for storage arease and containers:

Store in original container. CAUTION: Aerosol are under pressure. Keep away from direct sunlight and temperatures above  $50\,^{\circ}$  C. Do not apply force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry, cool and well ventilated place.

Storage regulations for aerosols!

Storage class: 2B, Aerosols

#### 7.3. Specific en use(s):

No data available.

#### 8. Exposure controls/personal protection

#### 8.1. Control parameters:

Components	CAS-No.	Control parameters		Excess factor	Base
		ml/m <sup>3</sup> (ppm)	mg/m <sup>3</sup>		
Hydrocarbons, C7, n-alkanes, iso-	/	200	1.000	4	

According to Regulation (EC) 1907/2006 and Regulation (EC) 453/2010 (REACH)

Version: 1.0

# BREMSENREINIGER

Revision date: 18.03.2014

alkanes, cyclic					
Acetone	67-64-1	500	1.210		
Carbon dioxide	124-38-9	5.000	9.000		
Propane	74-98-6	1.000	1.800	4	
Isobutane	75-28-5	1.000	2.400	4	

#### 8.2. Exposure controls:

### **Technical protective equipment:**

Provide sufficient air exchange and / or exhaust in work rooms.

### Personal protective equipment:

<u>Respiratory</u> At concentrations above the exposure limit they must use respiratory protection. Respirator with

<u>protection:</u> combination filter for particles and vapors (EN 141). Respirator with A filter.

<u>Hand protection:</u> The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the

preparation/the chemical mixture.

Eye protection: Tightly fitting safety goggles.

<u>Protective clothing:</u> Flame retardant antistatic protective clothing. Choose body protection according to the amount and

concentration of the hazardous substance at the workplace.

Hygien measures: Handle with good industrial hygiene and safety practice. General industrial hygiene measures. Do

not breathe spray. Contact with skin, eyes and clothing. When using do not eat, drink or smoke. Wash hands before breaks and after work. Skin protection plan note. Wash contaminated clothing

before reuse.

#### **Environmental exposure controls:**

General advice: Do not flush into surface water or sanitary sewer. Further leakage or spillage if possible without risk.

If the product contaminates rivers and lakes or drains inform respective authorities.

### 9. Physical and chemical properties

#### 9.1. Information on basis physical and chemical properties:

	Walue	Unit	At	Methode	Notice
Appearance:	aerosol				
Colour:	black				
Odour:	characteristic				
Flash point:	Cca80	$^{\circ}\mathrm{C}$			Isobutane
Ignition point:	56 – 110	$^{\circ}\mathrm{C}$			Acitive substance
Lower explosion limit:	1,4	Vol. %			
Upper explosion limit:	13,00	Vol. %			
Density:	0,722	g/cm <sup>3</sup>			Acitive substance
Water solubility:	unsoluble				
VOC:	702	g/l			
VOC:	96,69	%			
Organic solvents:	87,6	%			
0.2 Other information.					

#### 9.2. Other information:

No data available.

### 10. Stability and reactivity

#### 10.1. Reaktivity:

No data available.

### 10.2. Chemical stability:

According to Regulation (EC) 1907/2006 and Regulation (EC) 453/2010 (REACH)

Version: 1.0

### BREMSENREINIGER

Revision date: 18.03.2014

The product is chemical stable.

### 10.3. Possibility of hazardous reactions:

No decomposition if stored and applied. Vapors may form explosive mixtures with air. Because of the high vapor pressure when heated bursting of the vessels.

#### 10.4. Conditions to avoid:

Heat, flames and sparks.

#### 10.5. Incompatible materials:

No data available.

## 10.6. Hazardous decomposition products:

Hazardous

Possible in case of fire / high temperatures the formation of hazardous / toxic fumes.

decomposition products::

### 11. Toxicological information

#### Acute toxicity:

Acute oral toxicity:

Acetone  $LD_{50} > 2000 \text{ mg/kg (rat)}$ Hydrocarbons, C7, n-alkanes,  $LD_{50} > 8 \text{ ml/kg (rat)}$ 

iso-alkanes, cyclic

Acute inhalation toxicity:

Acetone  $LC_{50} > 20 \text{ mg/kg (rat)}$ 

Hydrocarbons, C7, n-alkanes,  $LC_{50} > 23,3 \text{ mg/l (rat, 4 h)}$ 

iso-alkanes, cyclic

Acute dermal toxicity:

 $LD_{50} > 2000 \text{ mg/kg (rat)}$ Acetone Hydrocarbons, C7, n-alkanes,  $LD_{50} > 4$  ml/kg (rat)

iso-alkanes, cyclic

Cause irritation.

Skin corrosion/irritation: Serious eye damage/eye

irritation:

May cause irritation.

Respiratory or skin

Possible sensitization through the skin.

sensitization:

Germ cell mutagenicity: No data available Carcinogenicity: No data available No data available Reproductive and

developmental toxicity:

Other information: Drowsiness and dizziness. Irritation and dermatitis, weakness.

### 12. Ecological information

#### 12.1. Toxicity:

Toxicity to fish:

Acetone LC/EC/IC50 > 1000 mg/l Hydrocarbons, C7, n-LL/EL/IL50 > 1 - <= 10 mg/l

alkanes, iso-alkanes,

cyclic

Toxicity to Dapnia:

Acetone LC/EC/IC50 > 1000 mg/l (Daphnia magna)

Hydrocarbons, C7, n-LL/EL/IL50 > 1 - <= 10 mg/l

According to Regulation (EC) 1907/2006 and Regulation (EC) 453/2010 (REACH)

Version: 1.0

### BREMSENREINIGER

Revision date: 18.03.2014

alkanes, iso-alkanes,

cyclic

Toxicity to algae:

Hydrocarbons, C7, n- LL/

LL/EL/IL50 > 10 - <= 100 mg/l

alkanes, iso-alkanes,

cyclic

Toxicity to bacteria:

Hydrocarbons, C7, n-

LL/EL/IL50 > 10 - <= 100 mg/l

alkanes, iso-alkanes,

cyclic

### 12.2. Persistenc and degradability:

No data available.

### 12.3. Bioaccumulative potencial:

No data available.

#### 12.4. Mobility in soil:

No data available.

#### 12.5. Results of PBT- and vPvB assesment:

No data available.

#### 12.6. Other adverse effects:

The penetration of the product into drains, water courses or the soil should be prevented.

### 13. Disposal considirations

#### 13.1. Product:

Waste key number: 160504\* = Accumulators containing certain dangerous gases in pressurized containers.

\* = The disposal must be provided.

Recommendation: Do not open, even after use or burn.

Disposal according to official regulations.

13.2. Packaging:

Waste key number: 150110 = Packaging containing residues of hazardous substances or

contaminated by dangerous substances

Recommendation: Drain thoroughly and completely as possible. Disposal according to official regulations.

### 14. Transport information

### ADR/RID

UN number: 1950

Product designation: AEROSOLS

Class: 2
Packaging group: -Code: 5F
Label: 2.1

Limited quantities: 1 L/LQ2

Special provisions: 190 - 327 - 625

Tunnel restriction code: (D)
Dangerous for the yes

environment:

### Besondere Vorsichtsmaßnahmen für den Verwender:

Vgl. Abschnitt: 6, 7 und 8

According to Regulation (EC) 1907/2006 and Regulation (EC) 453/2010 (REACH)

Version: 1.0

# **BREMSENREINIGER**

Revision date: 18.03.2014

## 15. Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture:

Council Directive		Quantity 1	Quantity 2
(96/82/EC):	Extremely flammable	10 t	50 t
	Dangerous for the environment	200 t	500 t
	Petroleum	2.500 t	25.000 t

### 15.2. Chemical safety assessment:

No data available.

### 16. Other information

### Full text of R-phrases referred to under sections 2 and 3:

R11	Highly flammable.
R12	Extremely flammable.
R36	Irritating to eyes.
R38	Irritating to skin.
R65	Harmful: May cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## Full text of H-statements referred to under sections 2 and 3:

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.